



ASHLAR

CABIN CREEK RIVER ROCK

GEOLOGY: dolomitic limestone

BASIC USE

exterior walls of buildings and fireplaces
stone shall be mortared in

COLOR RANGE

tumbled Chilton Custom Country Blend
white from tumbling

COLOR CONSISTENCY PER PALLET

somewhat consistent

WEIGHT CALCULATED IN INCHES

$l \times w \times h / 1728$ (inches cubed) $\times 170$
= approx 170 pounds per cubic foot

PALLET

FULL VENEER: 4,000 pounds
THIN VENEER: 10-15 lbs/ft²; Qty Bx or Sm Bx
Qty Bx - 100 sq ft flats and 50 lineal ft corners
Sm Bx - (24) 8 sq ft flats (192 sq ft) and
(20) 8 lineal ft corners (160 lineal ft)

FULL VENEER

COMMON COVERAGE *Est.(can vary)

Standard Joint	Drystack	Overgrout
40 square feet / ton	30 ft ² /ton	50 ft ² /ton

TUMBLING CHILTON COUNTRY SQUIRE

DIMENSIONS

US: inches (average)	METRIC: mm (average)
l: 6" to 24" (12")	l: 152 to 609 (355)
h: 1/2" to 8"	h: 13 to 203
w: 3" to 5" (4")	w: 76 to 127 (101)

TYPICAL PIECE

ends somewhat square; natural cleft top and bottom; back, face and sides split; stone is mostly rectangular - tumbled rounded edges

TUMBLING CHILTON RUSTIC

DIMENSIONS

US: inches (average)	METRIC: mm (average)
l: 6" to 24" (16")	l: 152 to 609 (406)
h: 1/2" to 8"	h: 13 to 203
w: 3" to 5" (4")	w: 76 to 127 (101)

TYPICAL PIECE

ends somewhat square; natural cleft top and bottom; weatheredge and seamface face; split back; sides either split or naturally square; stone is mostly rectangular - tumbled rounded edges

TUMBLING FULL COLOR CASTLE ROCK

DIMENSIONS

US: inches (average)	METRIC: mm (average)
l: 6" to 24" (16")	l: 152 to 609 (406)
h: 4" to 12"	h: 101 to 304
w: 3" to 5" (4")	w: 76 to 127 (101)

TYPICAL PIECE

ends somewhat square; split top, bottom, and sides; bedface face and back; stone is squares and rectangles - tumbled rounded edges

PART NUMBERS

FULL VENEER

part number: 1BSTBUE01505TN

THIN VENEER

qty bx flat: 1BTVBUE01028QB
sm bx flat: 1BTVBUE01028BX
qty bx corner: 1BTVBUE01527QB
sm bx corner: 1BTVBUE01527BX

THIN VENEER

COMMON COVERAGE PER BOX *Est.(can vary)

Standard Joint	Drystack	Overgrout
8 & 100 square feet	6 & 75 ft ²	10 & 110 ft ²

TUMBLING CHILTON COUNTRY SQUIRE

DIMENSIONS

US: inches (average)	METRIC: mm (average)
l: 6" to 24" (12")	l: 152 to 609 (304)
h: 1/2" to 8"	h: 12 to 203
w: 3/4" to 1-1/4" (1")	w: 19 to 31 (25)

corner return 3" to 5" cr: 76 to 127

TYPICAL PIECE

ends somewhat square; natural cleft top & bottom; face & sides split; sawn back; mostly rectangular stone - tumbled rounded edges

TUMBLING CHILTON RUSTIC

DIMENSIONS

US: inches (average)	METRIC: mm (average)
l: 6" to 24" (16")	l: 152 to 609 (406)
h: 1/2" to 8"	h: 12 to 203
w: 3/4" to 1-1/4" (1")	w: 19 to 31 (25)

corner return 3" to 5" cr: 76 to 127

TYPICAL PIECE

ends somewhat square; natural cleft top & bottom; weatheredge & seamface face; sawn back; sides split or naturally square; mostly rectangular stone - tumbled rounded edges

TUMBLING FULL COLOR CASTLE ROCK

DIMENSIONS

US: inches (average)	METRIC: mm (average)
l: 6" to 24" (16")	l: 152 to 609 (406)
h: 4" to 12"	h: 101 to 304
w: 3/4" to 1-1/4" (1")	w: 19 to 31 (25)

corner return 3" to 5" cr: 76 to 127

TYPICAL PIECE

ends somewhat square; split top, bottom & sides; bedface face; sawn back; stone is squares & rectangles-tumbled rounded edges

ASTM TESTING DATA

CHILTON C97 water absorption—0.08%
CHILTON C97 density—177.4 pcf
CHILTON C99 modulus of rupture—1,220 psi
CHILTON C170
compressive strength w/rift—50,560 psi
compressive strength across rift—38,090 psi
CHILTON C880 flexural strength—3,070 psi



www.buechelstone.com