



CUT STONE

ST. MARY CREAM (COLOR RANGES)

GEOLOGY: limestone

BASIC USE

unlimited cut stone applications including: panels, hearths and mantels, pier caps, sills, and custom items for specific needs

COLOR RANGE

light gray and cream; light veining; occasional flecks of light buff

COLOR CONSISTENCY PER PALLET

consistent

WEIGHT CALCULATED IN INCHES

$l \times w \times h / 1728$ (inches cubed) $\times 170$
= approx 170 pounds per cubic foot

PALLET

LBS / PALLET: as specified per order

RECOMMENDED FINISH OPTIONS

natural; sawn; sand; sandblast; bushhammer; rockface; eased edge; bullnose; & brushed

COMMON APPLICATIONS

ST. MARY CREAM

ACCESSORIES

accent pieces (e.g. quoins, keystones, light mounts) custom cut to project requirements

BALUSTERS & COLUMNS

custom cut per project with large stone lathe

DOOR & WINDOW SURROUNDS

basic and ornate options custom cut to spec; CAD shop dwgs available for job site approval

FIREPLACE SURROUNDS

standard and custom options; CAD dwgs available for job site approval; can be used stand alone and with stone or brick fireplaces

HEARTHES & MANTELS

ST. MARY CREAM

HEARTHES & MANTELS

large selection of standard (20x20 hearth options) and custom sizes available; wide range of colors and finishes; can be custom made for specific needs

STANDARD DIMENSIONS EXAMPLE

US: inches & feet	METRIC: mm & m
l: 8' (maximum)	l: 2-1/3 m (maximum)
h: 2-1/4" (standard)	h: 57 mm (standard)
d: per order	d: per order

note: radius available if specified; maximum recommended length is general rule of thumb for minimum 5-1/2" depth

TYPICAL PIECE

stone shape and finishing of face/ends to be specified per order

PIER CAPS & SILLS

ST. MARY CREAM

PIER CAPS

large selection of standard and custom sizes available; wide range of colors and finishes; can be custom made for specific needs

TYPICAL PIECE

ends square; stone shape(s) and finishing to be specified per order

SILLS

large selection of standard and custom sizes available; wide range of colors and finishes; can be custom made for specific needs

STANDARD DIMENSIONS EXAMPLE

US: inches & feet	METRIC: mm & m
l: 8' (maximum)	l: 2-1/3 m (maximum)
h: 2-1/4" (standard)	h: 57 mm (standard)
d: as specified	d: as specified

note: max recommended length is general rule of thumb for minimum 5-1/2" depth

TYPICAL PIECE

ends square; stone shape(s) and finishing to be specified per order

ASTM TESTING DATA

ST. MARY C97 water absorption—1.95%

ST. MARY C97 specific gravity—2.43

ST. MARY C170

compressive strength—9,696.6 psi

ST. MARY C880 flexural strength—1,869 psi



www.buechelstone.com