



DIMENSIONAL

INDIANA DIMENSIONAL

GEOLOGY: dolomitic limestone

BASIC USE

exterior walls of buildings and fireplaces
stone shall be mortared in

COLOR RANGE

gray, buff, and
silver-buff

COLOR CONSISTENCY PER PALLET

consistent

WEIGHT CALCULATED IN INCHES

$l \times w \times h / 1728$ (inches cubed) $\times 160$
= approx 160 pounds per cubic foot

PALLET

FULL VENEER: 4,000 pounds
THIN VENEER: 10-15 lbs/ft²; Qty Bx or Sm Bx
Qty Bx - 100 sq ft flats and 50 lineal ft corners
Sm Bx - (24) 8 sq ft flats (192 sq ft) and
(20) 8 lineal ft corners (160 lineal ft)

FULL VENEER

COMMON COVERAGE *Est.(can vary)

Standard Joint	Drystack	Overgrout
40 square feet / ton	30 ft ² /ton	50 ft ² /ton

INDIANA DIMENSIONAL

DIMENSIONS

US: inches (average) METRIC: mm (average)

l: 6" to 42" (24") l: 152 to 1066 (609)

h: 2-1/4"; h: 5"; h: 57; h: 127;

h: 7-3/4"; h: 10-1/2" h: 196; h: 266

w: 3" to 5" (4") w: 76 to 127 (101)

note: $\pm 1/8"$ on sawn heights

ADDITIONAL SIZES

other heights available:

US: inches METRIC: mm

h: 13-1/4"; h: 16"; h: 336; h: 406;

h: 18-3/4"; h: 21-1/2" h: 476; h: 546

TYPICAL BLEND

20 percent 2-1/4"; 40 percent 5";

30 percent 7-3/4"; 10 percent 10-1/2"

TYPICAL PIECE

ends square;

sawn top and bottom; sides are split;

bedface face and back;

stone is rectangular in appearance

with length longer than height

PART NUMBERS

FULL VENEER

part number: 1BSTBED60001TN

THIN VENEER

qty bx flat: 1BTVIND02002QB

sm bx flat: 1BTVIND02002BX

qty bx corner: 1BTVIND02502QB

sm bx corner: 1BTVIND02502BX

ASTM TESTING DATA

INDIANA C97 water absorption—4.84%

INDIANA C97 specific gravity—2.27 to 2.28

INDIANA C99 modulus of rupture

wet perpendicular—653 psi

wet parallel—727 psi

dry perpendicular—843 psi

dry parallel—784 psi

INDIANA C170 compressive strength

wet perpendicular—5,735 psi

wet parallel—4,693 psi

dry perpendicular—6,581 psi

dry parallel—5,845 psi

INDIANA C880 flexural strength

wet perpendicular—544 psi

wet parallel—556 psi

dry perpendicular—716 psi

dry parallel—706 psi

THIN VENEER

COMMON COVERAGE PER BOX *Est.(can vary)

Standard Joint	Drystack	Overgrout
8 & 100 square feet	6 & 75 ft ²	10 & 110 ft ²

INDIANA DIMENSIONAL

DIMENSIONS

US: inches (average) METRIC: mm (average)

l: 6" to 24" (12") l: 152 to 533 (304)

h: 2-1/4"; h: 5"; h: 57; h: 127;

h: 7-3/4"; h: 10-1/2" h: 196; h: 266

w: 3/4" to 1-1/4" (1") w: 19 to 31 (25)

corner return 3" to 5" cr: 76 to 127

note: $\pm 1/8"$ on sawn heights

ADDITIONAL SIZES

other heights available:

US: inches

h: 13-1/4"; h: 16";

h: 18-3/4"; h: 21-1/2"

TYPICAL BLEND

20 percent 2-1/4"; 40 percent 5";

30 percent 7-3/4"; 10 percent 10-1/2"

TYPICAL PIECE

ends square;

sawn top and bottom; sides are split;

bedface face and sawn back;

stone is rectangular in appearance

with length longer than height



www.buechelstone.com