

CUT STONE

MILL CREEK THERMALLED (COLOR RANGES)



GEOLOGY: limestone

BASIC USE

unlimited cut stone applications including:
panels, hearths and mantels, pier caps, sills,
and custom items for specific needs

COLOR RANGE

wide mottled range of gray, pink, and tan;
color variations common within a piece

COLOR CONSISTENCY PER PALLET

inconsistent

WEIGHT CALCULATED IN INCHES

$l \times w \times h / 1728$ (inches cubed) $\times 170$
= approx 170 pounds per cubic foot

PALLET

LBS / PALLET: as specified per order

RECOMMENDED FINISH OPTIONS

natural; sawn; sand; thermal; bushhammer;
rockface; and brushed



COMMON APPLICATIONS

MILL CREEK - THERMALLED FINISH ACCESSORIES

accent pieces (e.g. quoins, keystones, light
mounts) custom cut to project requirements

BALUSTERS & COLUMNS

custom cut per project with large stone lathe

DOOR & WINDOW SURROUNDS

basic and ornate options custom cut to spec;
CAD shop dwgs available for job site approval

FIREPLACE SURROUNDS

standard and custom options; CAD dwgs
available for job site approval; can be used
stand alone and with stone or brick fireplaces

COMMON APPLICATIONS

MILL CREEK - THERMALLED FINISH HEARTH & MANTELS

large selection of standard (20x20 hearth
options) and custom sizes available; wide
range of colors and finishes; can be custom
made for specific needs

STANDARD DIMENSIONS EXAMPLE

US: inches & feet	METRIC: mm & m
l: 8' (maximum)	l: 2-1/4 m (maximum)
h: 3" (minimum)	h: 203 mm (minimum)
d: 5-1/2" (minimum)	d: 140 mm (minimum)

note: max recommended length is general
rule of thumb for minimum 5-1/2" depth

TYPICAL PIECE

stone shape and finishing of face/ends to be
specified per order

PIER CAPS & SILLS

MILL CREEK - THERMALLED FINISH PIER CAPS

large selection of standard and custom sizes
available; wide range of colors and finishes;
can be custom made for specific needs

STANDARD DIMENSIONS EXAMPLE

US: inches	METRIC: mm
l: 24"	l: 610 mm
h: 3"	h: 76 mm
w: 24"	d: 610 mm

TYPICAL PIECE

ends square; stone shape(s) and finishing to
be specified per order

SILLS

large selection of standard and custom sizes
available; wide range of colors and finishes;
can be custom made for specific needs

STANDARD DIMENSIONS EXAMPLE

US: inches & feet	METRIC: mm & m
l: 4' (maximum)	l: 1-1/4 m (maximum)
h: 2-1/2" (minimum)	h: 64 mm (minimum)
d: per order	d: per order

TYPICAL PIECE

ends square; stone shape(s) and finishing to
be specified per order

ASTM TESTING DATA

MILL CREEK C97 water absorption—0.66%

MILL CREEK C97 density—173.0 pcf

MILL CREEK C99

modulus of rupture—2,072 psi

MILL CREEK C170

compressive strength—26,260 psi

MILL CREEK C880 flexural strength—1,374 psi



www.buechelstone.com