

MOSAIC

MILL CREEK WEBWALL



GEOLOGY: dolomitic limestone

BASIC USE

exterior walls of buildings and fireplaces
stone shall be mortared in

COLOR RANGE

brown to buff

COLOR CONSISTENCY PER PALLET

consistent

WEIGHT CALCULATED IN INCHES

$l \times w \times h / 1728$ (inches cubed) $\times 170$
= approx 170 pounds per cubic foot

PALLET

FULL VENEER: 4,000 pounds
THIN VENEER: 10-15 lbs/ft²; Qty Bx or Sm Bx
Qty Bx - 100 sq ft flats and 50 lineal ft corners
Sm Bx - (24) 8 sq ft flats (192 sq ft) and
(20) 8 lineal ft corners (160 lineal ft)



FULL VENEER

COMMON COVERAGE *Est.(can vary)

| Standard Joint | Drystack | Overgrout |
|----------------------|-------------------------|-------------------------|
| 40 square feet / ton | 30 ft ² /ton | 50 ft ² /ton |

MILL CREEK WEBWALL

DIMENSIONS

| US: inches (average) | METRIC: mm (average) |
|----------------------|----------------------|
|----------------------|----------------------|

| | |
|-------------------|-------------------|
| l: 3" to 16" dia. | l: 76 to 406 dia. |
|-------------------|-------------------|

| | |
|-------------------|-------------------|
| h: 3" to 16" dia. | h: 76 to 406 dia. |
|-------------------|-------------------|

| | |
|------------------|--------------------|
| w: 3" to 5" (4") | w: 76 to 127 (101) |
|------------------|--------------------|

note: lengths and heights are irregular shapes
3 inches to 16 inches in diameter

TYPICAL PIECE

ends irregular;
natural split sides;
bedface face and back;
stone is random shapes

PART NUMBERS

FULL VENEER

part number: 1BSTLEN01007TN

THIN VENEER

qty bx flat: 1BTVLEN01006QB
sm bx flat: 1BTVLEN01006BX
qty bx corner: 1BTVLEN01506QB
sm bx corner: 1BTVLEN01506BX

THIN VENEER

COMMON COVERAGE PER BOX *Est.(can vary)

| Standard Joint | Drystack | Overgrout |
|---------------------|------------------------|--------------------------|
| 8 & 100 square feet | 6 & 75 ft ² | 10 & 110 ft ² |

MILL CREEK WEBWALL

DIMENSIONS

| US: inches (average) | METRIC: mm (average) |
|----------------------|----------------------|
|----------------------|----------------------|

| | |
|-------------------|-------------------|
| l: 3" to 12" dia. | l: 76 to 304 dia. |
|-------------------|-------------------|

| | |
|-------------------|-------------------|
| h: 3" to 12" dia. | h: 76 to 304 dia. |
|-------------------|-------------------|

| | |
|------------------------|------------------|
| w: 3/4" to 1-1/4" (1") | w: 19 to 31 (25) |
|------------------------|------------------|

corner return 3" to 5" cr: 76 to 127

note: lengths and heights are irregular shapes
3 inches to 12 inches in diameter

TYPICAL PIECE

ends irregular;
natural split sides;
bedface face and sawn back;
stone is random shapes

ASTM TESTING DATA

MILL CREEK C97 water absorption—0.66%

MILL CREEK C97 density—173.0 pcf

MILL CREEK C99

modulus of rupture—2,072 psi

MILL CREEK C170

compressive strength—26,260 psi

MILL CREEK C880 flexural strength—1,374 psi



www.buechelstone.com