

LEDGESTONE

WHISPERING PINES LEDGESTONE



GEOLOGY: sandstone

BASIC USE

exterior walls of buildings and fireplaces
stone shall be mortared in

COLOR RANGE

greens, blues, and browns

COLOR CONSISTENCY PER PALLET

consistent

WEIGHT CALCULATED IN INCHES

$l \times w \times h / 1728$ (inches cubed) $\times 165$
= approx 165 pounds per cubic foot

PALLET

FULL VENEER: 3,000 pounds
THIN VENEER: 10-15 lbs/ft²; Qty Bx or Sm Bx
Qty Bx - 100 sq ft flats and 50 lineal ft corners
Sm Bx - (24) 8 sq ft flats (192 sq ft) and
(20) 8 lineal ft corners (160 lineal ft)

FULL VENEER

COMMON COVERAGE *Est.(can vary)

Standard Joint	Drystack	Overgrout
40 square feet / ton	30 ft ² /ton	50 ft ² /ton

WHISPERING PINES LEDGESTONE

DIMENSIONS

US: inches (average)	METRIC: mm (average)
l: 6" to 24" (12")	l: 152 to 609 (304)
h: 1" to 4"	h: 25 to 101
w: 3" to 5" (4")	w: 76 to 127 (101)

TYPICAL PIECE

ends random;
natural cleft top and bottom;
back, face, and sides split;
stone is mostly rectangular



PART NUMBERS

FULL VENEER

part number: 1BSTCAT01001TN

THIN VENEER

qty bx flat: 1BTVCAT01001QB
sm bx flat: 1BTVCAT01001BX
qty bx corner: 1BTVCAT01501QB
sm bx corner: 1BTVCAT01501BX

THIN VENEER

COMMON COVERAGE PER BOX *Est.(can vary)

Standard Joint	Drystack	Overgrout
8 & 100 square feet	6 & 75 ft ²	10 & 110 ft ²

WHISPERING PINES LEDGESTONE

DIMENSIONS

US: inches (average)	METRIC: mm (average)
l: 6" to 24" (12")	l: 152 to 609 (304)
h: 1" to 4"	h: 25 to 101
w: 3/4" to 1-1/4" (1")	w: 19 to 31 (25)

TYPICAL PIECE

ends random;
natural cleft top and bottom;
face and sides split; back is sawn;
stone is mostly rectangular

ASTM TESTING DATA

WHISPERING PINES C97

water absorption—0.96%

WHISPERING PINES C97

specific gravity—2.65

WHISPERING PINES C99

modulus of rupture—4,550 psi

WHISPERING PINES C170

compressive strength—11,630 psi

WHISPERING PINES C880

flexural strength—2,120 psi



www.buechelstone.com