



CUT STONE

CARAMEL CAPPUCCINO (COLOR RANGES)

GEOLOGY: limestone

BASIC USE

unlimited cut stone applications including: panels, hearths and mantels, pier caps, sills, and custom items for specific needs

COLOR RANGE

white, cream, caramel, with occasional fossils; somewhat variegated unless specified per project

COLOR CONSISTENCY PER PALLET

somewhat consistent

WEIGHT CALCULATED IN INCHES

$l \times w \times h / 1728$ (inches cubed) $\times 170$
= approx 170 pounds per cubic foot

PALLET

LBS / PALLET: as specified per order

RECOMMENDED FINISH OPTIONS

sawn; sand; sandblast; bushhammer; rock-face; eased edge; brushed, and bullnose



COMMON APPLICATIONS

CARAMEL CAPPUCCINO

ACCESSORIES

accent pieces (e.g. quoins, keystones, light mounts) custom cut to project requirements

BALUSTERS & COLUMNS

custom cut per project with large stone lathe

DOOR & WINDOW SURROUNDS

basic and ornate options custom cut to spec; CAD shop dwgs available for job site approval

FIREPLACE SURROUNDS

standard and custom options; CAD dwgs available for job site approval; can be used stand alone and with stone or brick fireplaces

HEARTH & MANTELS

CARAMEL CAPPUCCINO

HEARTH & MANTELS

large selection of custom sizes available; wide range of colors and finishes; can be custom made for specific needs

STANDARD DIMENSIONS EXAMPLE

US: inches & feet	METRIC: mm & m
l: 6' (maximum)	l: 1-3/4 m (maximum)
h: 2-1/4" (standard)	h: 57 mm (standard)
d: as specified	d: as specified

note: radius available if specified

TYPICAL PIECE

stone shape and finishing of face/ends to be specified per order

PIER CAPS & SILLS

CARAMEL CAPPUCCINO

PIER CAPS

large selection of standard and custom sizes available; wide range of colors and finishes; can be custom made for specific needs

TYPICAL PIECE

ends square; stone shape(s) and finishing to be specified per order

SILLS

large selection of standard and custom sizes available; wide range of colors and finishes; can be custom made for specific needs

STANDARD DIMENSIONS EXAMPLE

US: inches & feet	METRIC: mm & m
l: 6' & l: 4' (maximum)	l: 1-3/4 m & l: 1-1/4 m
h: 2-1/4" (standard)	h: 57 mm (standard)
d: 5-1/2" & d: 2-1/2"	d: 140 mm & d: 63 mm

note: max recommended lengths are general rules of thumb for 5-1/2" & 2-1/2" depths

TYPICAL PIECE

ends square; stone shape(s) and finishing to be specified per order

ASTM TESTING DATA

CARAMEL CAPPUCCINO C97

water absorption—6.13%

CARAMEL CAPPUCCINO C97

density—136.8 pcf

CARAMEL CAPPUCCINO C97

specific gravity—2.193

CARAMEL CAPPUCCINO C99

modulus of rupture—824 psi

CARAMEL CAPPUCCINO C170

compressive strength—6,560 psi



www.buechelstone.com