

## OUTCROPPING STEPS

### CHILTON WEATHEREDGE OUTCROPPING STEPS



**GEOLOGY:** dolomitic limestone

**BASIC USE**  
for steps

**COLOR RANGE**  
top or bottom is purple, lavender, mauve,  
gray, buff, blue, and brown;  
face is brown, buff, orange, yellow, red, & rust

**COLOR CONSISTENCY PER PALLET**  
somewhat consistent

**WEIGHT CALCULATED IN INCHES**  
 $l \times w \times h / 1728$  (inches cubed)  $\times 170$   
= approx 170 pounds per cubic foot

**PALLET**  
4,000 pounds



## OUTCROPPING STEPS

### COVERAGES

coverages calculated as specified per project

### CHILTON WEATHEREDGE

### OUTCROPPING STEPS

#### DIMENSIONS

US: inches	METRIC: mm
l: 18" to 60"	l: 457 to 1524 mm
h: 5" to 8"	h: 127 to 203 mm
w: 18" to 60"	w: 457 to 1524 mm

note: lengths and widths are irregular shapes  
18 inches to 60 inches in diameter

## PART NUMBERS

part number: 1OUTBUE01004TN

## OUTCROPPING STEPS

### CHILTON WEATHEREDGE

### OUTCROPPING STEPS

#### TYPICAL PIECE

ends irregular;  
natural cleft top and bottom;  
natural split sides with at least one face  
being seamface or weatheredge;  
stone is somewhat square but  
may be irregular

## ASTM TESTING DATA

CHILTON C97 water absorption—0.08%  
CHILTON C97 density—177.4 pcf  
CHILTON C99 modulus of rupture—1,220 psi  
CHILTON C170  
compressive strength w/rift—50,560 psi  
compressive strength across rift—38,090 psi  
CHILTON C880 flexural strength—3,070 psi

