



## OUTCROPPINGS

### DESERT OUTCROPPINGS



**GEOLOGY:** sandstone

#### BASIC USE

for retaining ground or  
as an accent in landscaping

#### COLOR RANGE

brown to tan

#### COLOR CONSISTENCY PER PALLET

somewhat consistent

#### WEIGHT CALCULATED IN INCHES

$l \times w \times h / 1728$  (inches cubed)  $\times 165$   
= approx 165 pounds per cubic foot

#### PALLET

4,000 pounds

## OUTCROPPINGS

#### PALLETS

2 to 3 man: 10 to 12 pieces per pallet

#### COVERAGES

coverages calculated as specified per project

#### DESERT 2 to 3 MAN

#### OUTCROPPINGS

##### DIMENSIONS

**US: inches**

l: 24" to 36"

h: 4" to 8"

w: 24" to 36"

note: lengths and widths are irregular shapes

24 inches to 36 inches in diameter

##### TYPICAL PIECE

ends irregular;

natural cleft top and bottom;

natural split sides;

stone is random shapes

**METRIC: mm**

l: 610 to 914 mm

h: 101 to 203 mm

w: 610 to 914 mm

## PART NUMBERS

#### DESERT OUTCROPPINGS

part number 2 to 3 man: 1OUTSAN01010TN

part number outcroppings:

1OUTSAN01011TN

## OUTCROPPINGS

#### PALLETS

standard size: 3 to 5 pieces per pallet

#### COVERAGES

coverages calculated as specified per project

#### DESERT OUTCROPPINGS

##### DIMENSIONS

**US: inches**

l: 18" to 60"

h: 5" to 12"

w: 18" to 60"

note: lengths and widths are irregular shapes

18 inches to 60 inches in diameter

##### TYPICAL PIECE

ends irregular;

natural cleft top and bottom;

natural split sides;

stone is random shapes

**METRIC: mm**

l: 457 to 1524 mm

h: 127 to 304 mm

w: 457 to 1524 mm

## ASTM TESTING DATA

DESERT C97 water absorption—0.6%

DESERT C97 density—157.7 pcf

DESERT C99 modulus of rupture—2,000 psi

DESERT C170

compressive strength w/rift—32,550 psi

compressive strength across rift—31,160 psi

DESERT C880 flexural strength—1,910 psi

DESERT C241 abrasion resistance—48.27



www.buechelstone.com