

COBBLES AND BOULDERS

FOND DU LAC WEATHERED BOULDERS



GEOLOGY: dolomitic limestone

BASIC USE

accents for landscaping

COLOR RANGE

brown to buff

COLOR CONSISTENCY PER PALLET

consistent

WEIGHT CALCULATED IN INCHES

l x w x h / 1728 (inches cubed) x 170
= approx 170 pounds per cubic foot

PALLET

as specified per project



24" to 60"

COVERAGES

coverages calculated as specified per project

FOND DU LAC WEATHERED BOULDERS

DIMENSIONS

US: inches

l: 20" to 60"

h: 12" to 30"

w: 20" to 48"

METRIC: mm

l: 508 to 1524 mm

h: 304 to 762 mm

w: 508 to 1219 mm

TYPICAL PIECE

ends irregular;

natural cleft top and bottom;

natural split, seamface, or weatheredge sides;

stone is random wavy shapes

PART NUMBERS

24" to 60"

part number: 1WBOB02005TN

12" to 24"

part number: 1WBOB02006TN

12" to 24"

COVERAGES

coverages calculated as specified per project

FOND DU LAC WEATHERED BOULDERS

DIMENSIONS

US: inches

l: 12" to 30"

h: 12" to 30"

w: 12" to 30"

METRIC: mm

l: 304 to 762 mm

h: 304 to 762 mm

w: 304 to 762 mm

TYPICAL PIECE

ends irregular;

natural cleft top and bottom;

natural split, seamface, or weatheredge sides;

stone is random wavy shapes

ASTM TESTING DATA

FOND DU LAC C97 water absorption—0.36%

FOND DU LAC C97 density—174.2 pcf

FOND DU LAC C99

modulus of rupture—1,470 psi

FOND DU LAC C170

compressive strength w/rift—29,040 psi

compressive strength across rift—34,240 psi

FOND DU LAC C880

flexural strength—1,740 psi



www.buechelstone.com