



LEDGESTONE

**GRAY
TAILORED
LEDGESTONE**

GEOLOGY: dolomitic limestone

BASIC USE

exterior walls of buildings and fireplaces
stone shall be mortared in

COLOR RANGE

light gray to white

COLOR CONSISTENCY PER PALLET

consistent

WEIGHT CALCULATED IN INCHES

$l \times w \times h / 1728$ (inches cubed) $\times 170$
= approx 170 pounds per cubic foot

PALLET

FULL VENEER: 4,000 pounds
THIN VENEER: 10-15 lbs/ft²; Qty Bx or Sm Bx
Qty Bx - 100 sq ft flats and 50 lineal ft corners
Sm Bx - (24) 8 sq ft flats (192 sq ft) and
(20) 8 lineal ft corners (160 lineal ft)

THIN VENEER

GRAY TAILORED LEDGESTONE

TYPICAL BLEND

100 percent splitface face;
face of stone cannot have a sawn finish

TYPICAL PIECE

ends sawn random lengths; sawn top,
bottom, and sides; face is splitface; back
sawn; stone is linear squares and rectangles

PART NUMBERS

FULL VENEER

part number: N/A

THIN VENEER

qty bx flat: 1BTVBUE02069QB
sm bx flat: 1BTVBUE02069BX
qty bx corner: 1BTVBUE02569QB
sm bx corner: 1BTVBUE02569BX

THIN VENEER

COMMON COVERAGE PER BOX*Est.(can vary)

Figured for Drystack Joint Only
8 & 100 square feet

GRAY TAILORED LEDGESTONE

DIMENSIONS

US: inches (average) **METRIC: mm (average)**

l: 4" to 16" (8") l: 100 to 400 (203)

h: 1"; h: 2"; h: 4" h: 25; h: 51; h: 102

w: 3/4" to 1-1/4" (1") w: 19 to 38 (25)

corner return N/A cr: N/A

CORNER INSTALLATION



ASTM TESTING DATA

GRAY C97 water absorption—0.36%

GRAY C97 density—174.2 pcf

GRAY C99 modulus of rupture—1,470 psi

GRAY C170

compressive strength w/rift—29,040 psi

compressive strength across rift—34,240 psi

GRAY C880 flexural strength—1,740 psi



www.buechelstone.com