



## FIELDLEDGE

### WHISPERING PINES PIONEER BLEND

**GEOLOGY:** sandstone

#### BASIC USE

exterior walls of buildings and fireplaces  
stone shall be mortared in

#### COLOR RANGE

75% Whispering Pines LedgeStone  
25% Whispering Pines Fieldstone

#### COLOR CONSISTENCY PER PALLET

somewhat consistent

#### WEIGHT CALCULATED IN INCHES

$l \times w \times h / 1728$  (inches cubed)  $\times 165$   
= approx 165 pounds per cubic foot

#### PALLET

FULL VENEER: 4,000 pounds  
THIN VENEER: 10-15 lbs/ft<sup>2</sup>; Qty Bx or Sm Bx  
Qty Bx - 100 sq ft flats and 50 lineal ft corners  
Sm Bx - (24) 8 sq ft flats (192 sq ft) and  
(20) 8 lineal ft corners (160 lineal ft)

### FULL VENEER

#### COMMON COVERAGE \*Est.(can vary)

Standard Joint	Drystack	Overgrout
40 square feet / ton	30 ft <sup>2</sup> /ton	50 ft <sup>2</sup> /ton

#### WHISPERING PINES LEDGESTONE

##### DIMENSIONS

<b>US: inches (average)</b>	<b>METRIC: mm (average)</b>
l: 6" to 24" (12")	l: 152 to 609 (304)
h: 1" to 4"	h: 25 to 101
w: 3" to 5" (4")	w: 76 to 127 (101)

##### TYPICAL PIECE

ends random;  
natural cleft top and bottom;  
back, face and sides split;  
stone is mostly rectangular

#### WHISPERING PINES FIELDSTONE

##### DIMENSIONS

<b>US: inches (average)</b>	<b>METRIC: mm (average)</b>
l: 3" to 16" dia.	l: 76 to 406 dia.
h: 3" to 16" dia.	h: 76 to 406 dia.
w: 3" to 5" (4")	w: 76 to 127 (101)

note: lengths and heights are irregular shapes  
3 inches to 16 inches in diameter

##### TYPICAL PIECE

ends irregular;  
natural split sides;  
bedface face and back;  
stone is random shapes

### PART NUMBERS

#### FULL VENEER

part number: 1BSTCAT01003TN

#### THIN VENEER

qty bx flat: 1BTVCAT01003QB  
sm bx flat: 1BTVCAT01003BX  
qty bx corner: 1BTVCAT01503QB  
sm bx corner: 1BTVCAT01503BX

### THIN VENEER

#### COMMON COVERAGE PER BOX \*Est.(can vary)

Standard Joint	Drystack	Overgrout
8 & 100 square feet	6 & 75 ft <sup>2</sup>	10 & 110 ft <sup>2</sup>

#### WHISPERING PINES LEDGESTONE

##### DIMENSIONS

<b>US: inches (average)</b>	<b>METRIC: mm (average)</b>
l: 6" to 24" (12")	l: 152 to 609 (304)
h: 1" to 4"	h: 25 to 101
w: 3/4" to 1-1/4" (1")	w: 19 to 31 (25)

corner return 3" to 5" cr: 76 to 127

##### TYPICAL PIECE

ends random;  
natural cleft top and bottom;  
face and sides split; sawn back;  
stone is mostly rectangular

#### WHISPERING PINES FIELDSTONE

##### DIMENSIONS

<b>US: inches (average)</b>	<b>METRIC: mm (average)</b>
l: 3" to 16" dia.	l: 76 to 406 dia.
h: 3" to 16" dia.	h: 76 to 406 dia.
w: 3/4" to 1-1/4" (1")	w: 19 to 31 (25)

corner return 3" to 5" cr: 76 to 127  
note: lengths and heights are irregular shapes  
3 inches to 16 inches in diameter

##### TYPICAL PIECE

ends irregular;  
natural split sides;  
bedface face and sawn back;  
stone is random shapes

### ASTM TESTING DATA

#### WHISPERING PINES C97

water absorption—0.96%

#### WHISPERING PINES C97

specific gravity—2.65

#### WHISPERING PINES C99

modulus of rupture—4,550 psi

#### WHISPERING PINES C170

compressive strength—11,630 psi

#### WHISPERING PINES C880

flexural strength—2,120 psi



www.buechelstone.com