

## TAILORED FIELDLEDGE

### SPALTED OAK TAILORED FIELDLEDGE



**GEOLOGY:** schist

#### BASIC USE

exterior walls of buildings and fireplaces  
stone shall be mortared in

#### COLOR RANGE

grays, tans, charcoals, whites, buffs, blues,  
dark grays, beiges with occasional oranges,  
browns, and blacks

#### COLOR CONSISTENCY PER PALLET

somewhat consistent

#### WEIGHT CALCULATED IN INCHES

$l \times w \times h / 1728$  (inches cubed)  $\times 170$   
= approx 170 pounds per cubic foot

#### PALLET

FULL VENEER: N/A (Natural Thin Veneer Only)  
THIN VENEER: 10-15 lbs/ft<sup>2</sup>; Qty Bx or Sm Bx  
Qty Bx - 100 sq ft flats and 50 lineal ft corners  
Sm Bx - (24) 8 sq ft flats (192 sq ft) and  
(20) 8 lineal ft corners (160 lineal ft)

## FULL VENEER (N/A)

### SPALTED OAK TAILORED FIELDLEDGE

#### NTV (NATURAL THIN VENEER) ONLY

Spalted Oak Tailored Fieldledge is a Thin Veneer product only; so there is no applicable Full Veneer spec information to report. Please find detailed data for this Thin Veneer product listed in the far right column. Thank you.



## PART NUMBERS

### FULL VENEER

part number: N/A

#### THIN VENEER

qty bx flat: 1BTVGRA03062QB  
sm bx flat: 1BTVGRA03062BX  
qty bx corner: 1BTVGRA03562QB  
sm bx corner: 1BTVGRA03562BX

## THIN VENEER

### COMMON COVERAGE PER BOX <sup>\*Est.(can vary)</sup>

Figured for Drystack Joint Only  
8 & 100 square feet

### SPALTED OAK TAILORED FIELDLEDGE

#### DIMENSIONS

**US: inches (average)**    **METRIC: mm (average)**

l: 3" to 24" dia.    l: 76 to 610 dia.

h: 2"; h: 4"; h: 6"    h: 51; h: 102; h: 152

w: 3/4" to 1-1/4" (1")    w: 19 to 31 (25)

corner return N/A    cr: N/A

note: sawn heights with varying lengths  
having rough irregular ends

#### TYPICAL PIECE

ends irregular; random lengths;  
sawn top and bottom; sides not square;  
bedface face and sawn back;  
overall appearance of stone will be linear  
when installed

#### CORNER INSTALLATION

