

TAILORED FIELDLEDGE

SPALTED OAK TAILORED FIELDLEDGE



GEOLOGY: schist

BASIC USE

exterior walls of buildings and fireplaces
stone shall be mortared in

COLOR RANGE

grays, tans, charcoals, whites, buffs, blues,
dark grays, beiges with occasional oranges,
browns, and blacks

COLOR CONSISTENCY PER PALLET

somewhat consistent

WEIGHT CALCULATED IN INCHES

$l \times w \times h / 1728$ (inches cubed) $\times 170$
= approx 170 pounds per cubic foot

PALLET

FULL VENEER: N/A (Natural Thin Veneer Only)
THIN VENEER: 10-15 lbs/ft²; Qty Bx or Sm Bx
Qty Bx - 100 sq ft flats and 50 lineal ft corners
Sm Bx - (24) 8 sq ft flats (192 sq ft) and
(20) 8 lineal ft corners (160 lineal ft)



FULL VENEER (N/A)

SPALTED OAK TAILORED FIELDLEDGE

NTV (NATURAL THIN VENEER) ONLY

Spalted Oak Tailored Fieldledge is a Thin Veneer product only; so there is no applicable Full Veneer spec information to report. Please find detailed data for this Thin Veneer product listed in the far right column. Thank you.

PART NUMBERS

FULL VENEER

part number: N/A

THIN VENEER

qty bx flat: 1BTVGRA03062QB
sm bx flat: 1BTVGRA03062BX
qty bx corner: 1BTVGRA03562QB
sm bx corner: 1BTVGRA03562BX

ASTM TESTING DATA

HIGHLAND SCOTCH | BARNWOOD BLUE C97
water absorption—1.4% | 0.5%

HIGHLAND SCOTCH | BARNWOOD BLUE C97
specific gravity—2.54 | 2.75

HIGHLAND SCOTCH | BARNWOOD BLUE C97
density—158.4 pcf | 171.8 pcf

HIGHLAND SCOTCH | BARNWOOD BLUE C99
modulus of rupture perpendicular
dry—2,460 psi | 3,490 psi

modulus of rupture perpendicular
wet—2,050 psi | 2,920 psi

modulus of rupture parallel
wet—1,308 psi | n/a

HIGHLAND SCOTCH | BARNWOOD BLUE C170
compressive strength parallel
dry—n/a | 12,260 psi

compressive strength parallel
wet—14,180 psi | 9,770 psi

compressive strength perpendicular
wet—12,920 psi | 11,220 psi

compressive strength perpendicular
dry—n/a | 15,300 psi

THIN VENEER

COMMON COVERAGE PER BOX *Est.(can vary)

Standard Joint	Drystack	Overgrout
8 & 100 square feet	6 & 75 ft ²	10 & 110 ft ²

SPALTED OAK TAILORED FIELDLEDGE

DIMENSIONS

US: inches (average)	METRIC: mm (average)
-----------------------------	-----------------------------

l: 3" to 24" dia. l: 76 to 610 dia.

h: 2"; h: 4"; h: 6" h: 51; h: 102; h: 152

w: 3/4" to 1-1/4" (1") w: 19 to 31 (25)

corner return N/A cr: N/A

note: sawn heights with varying lengths
having rough irregular ends

TYPICAL PIECE

ends irregular; random lengths;
sawn top and bottom; sides not square;
bedface face and sawn back;
overall appearance of stone will be linear
when installed

CORNER INSTALLATION

