

STEPS

CHILTON OUTCROPPING STEPS



GEOLOGY: dolomitic limestone

BASIC USE
for steps

COLOR RANGE
top or bottom is purple, lavender, mauve,
gray, buff, blue, and brown;
face is gray to charcoal with occasional
mauves

COLOR CONSISTENCY PER PALLET
somewhat consistent

WEIGHT CALCULATED IN INCHES
 $l \times w \times h / 1728$ (inches cubed) $\times 170$
= approx 170 pounds per cubic foot

PALLET
4,000 pounds



OUTCROPPING STEPS

COVERAGES

coverages calculated as specified per project

CHILTON OUTCROPPING STEPS

DIMENSIONS

US: inches

l: 18" to 60"

h: 5" to 8"

w: 18" to 60"

note: lengths and widths are irregular shapes

18 inches to 60 inches in diameter

METRIC: mm

l: 457 to 1524 mm

h: 127 to 203 mm

w: 457 to 1524 mm

PART NUMBERS

part number: 1OUTBUE01006TN

OUTCROPPING STEPS

CHILTON OUTCROPPING STEPS

TYPICAL PIECE

ends irregular;
natural cleft top and bottom;
natural split sides;
stone is somewhat square but
may be irregular

ASTM TESTING DATA

CHILTON C97 water absorption—0.08%

CHILTON C97 density—177.4 pcf

CHILTON C99 modulus of rupture—1,220 psi

CHILTON C170

compressive strength w/rift—50,560 psi

compressive strength across rift—38,090 psi

CHILTON C880 flexural strength—3,070 psi

