

PATIO & PAVING

FOND DU LAC FLAGSTONE



GEOLOGY: dolomitic limestone

BASIC USE

on patios and walkways; stone is dryset in gravel (screenings) bed or mortared in

COLOR RANGE

gray, light gray, buff, and white

COLOR CONSISTENCY PER PALLET

somewhat consistent

WEIGHT CALCULATED IN INCHES

l x w x h / 1728 (inches cubed) x 170
= approx 170 pounds per cubic foot

PALLET

4,000 pounds

PATIO & PAVING

COMMON COVERAGE *Est.(can vary)

1" to 2" height 1-3/4" to 2-1/2" ht.
80 square feet / ton 65 square feet / ton

FOND DU LAC FLAGSTONE

DIMENSIONS

US: inches	METRIC: mm
l: 18" to 48"	l: 457 to 1219 mm
h: 1" to 2" or	h: 25 to 51 mm or
h: 1-3/4" to 2-1/2"	h: 44 to 63 mm
w: 18" to 48"	w: 457 to 1219 mm

note: lengths and widths are irregular shapes
18 inches to 48 inches in diameter

PART NUMBERS

part no. 1" to 2": 1PATBUE02012TN
part no. 1-3/4" to 2-1/2": 1PATBUE02018TN

PATIO & PAVING

FOND DU LAC FLAGSTONE

TYPICAL PIECE

ends irregular;
natural cleft top and bottom;
natural split sides;
stone is random shapes

ASTM TESTING DATA

FOND DU LAC C97 water absorption—0.36%
FOND DU LAC C97 density—174.2 pcf
FOND DU LAC C99
modulus of rupture—1,470 psi
FOND DU LAC C170
compressive strength w/rift—29,040 psi
compressive strength across rift—34,240 psi
FOND DU LAC C880
flexural strength—1,740 psi