

STEPS

FOND DU LAC OUTCROPPING STEPS



GEOLOGY: dolomitic limestone

BASIC USE
for steps

COLOR RANGE
gray, light gray to white, buff

COLOR CONSISTENCY PER PALLET
somewhat consistent

WEIGHT CALCULATED IN INCHES
l x w x h / 1728 (inches cubed) x 170
= approx 170 pounds per cubic foot

PALLET
4,000 pounds



OUTCROPPING STEPS

COVERAGES

coverages calculated as specified per project
FOND DU LAC OUTCROPPING STEPS

DIMENSIONS

US: inches	METRIC: mm
l: 18" to 60"	l: 457 to 1524 mm
h: 5" to 8"	h: 127 to 203 mm
w: 18" to 60"	w: 457 to 1524 mm

note: lengths and widths are irregular shapes
18 inches to 60 inches in diameter

PART NUMBERS

part number: 1OUTBUE02006TN

OUTCROPPING STEPS

FOND DU LAC OUTCROPPING STEPS

TYPICAL PIECE
ends irregular;
natural cleft top and bottom;
natural split sides;
stone is somewhat square but
may be irregular

ASTM TESTING DATA

FOND DU LAC C97 water absorption—0.36%
FOND DU LAC C97 density—174.2 pcf
FOND DU LAC C99
modulus of rupture—1,470 psi
FOND DU LAC C170
compressive strength w/rift—29,040 psi
compressive strength across rift—34,240 psi
FOND DU LAC C880
flexural strength—1,740 psi