



## OUTCROPPINGS

### FOND DU LAC WEATHEREDGE OUTCROPPINGS



**GEOLOGY:** dolomitic limestone

#### BASIC USE

for retaining ground or  
as an accent in landscaping

#### COLOR RANGE

gray, light gray to white, buff;  
face is brown, buff, tan, and gold

#### COLOR CONSISTENCY PER PALLET

consistent

#### WEIGHT CALCULATED IN INCHES

$l \times w \times h / 1728$  (inches cubed)  $\times 170$   
= approx 170 pounds per cubic foot

#### PALLET

4,000 pounds

## OUTCROPPINGS

### PALLETS

1 to 2 man: 16 to 18 pieces per pallet;  
2 to 3 man: 10 to 12 pieces per pallet

### COVERAGES

coverages calculated as specified per project

### FOND DU LAC WEATHEREDGE

#### 1 to 2 MAN OUTCROPPINGS

##### DIMENSIONS

<b>US: inches</b>	<b>METRIC: mm</b>
l: 12" to 30"	l: 304 to 762 mm
h: 4" to 8"	h: 101 to 203 mm
w: 12" to 30"	w: 304 to 762 mm

note: lengths and widths are irregular shapes  
12 inches to 30 inches in diameter

### FOND DU LAC WEATHEREDGE

#### 2 to 3 MAN OUTCROPPINGS

##### DIMENSIONS

<b>US: inches</b>	<b>METRIC: mm</b>
l: 24" to 36"	l: 610 to 914 mm
h: 4" to 8"	h: 101 to 203 mm
w: 24" to 36"	w: 610 to 914 mm

note: lengths and widths are irregular shapes  
24 inches to 36 inches in diameter

##### TYPICAL PIECE

ends irregular;  
natural cleft top and bottom;  
natural split sides with at least one face  
being seamface or weatheredge;  
stone is random shapes

## PART NUMBERS

### FOND DU LAC WEATHEREDGE

#### OUTCROPPINGS

part number 1 to 2 man: 1OUTBUE02017TN  
part number 2 to 3 man: 1OUTBUE02010TN

part number outcroppings:

1OUTBUE02002TN

part number outcroppings 5" to 8":

1OUTBUE02018TN

## OUTCROPPINGS

### PALLETS

standard size: 3 to 5 pieces per pallet;  
5 to 8 inches thick: 3 to 5 pieces per pallet

### COVERAGES

coverages calculated as specified per project

### FOND DU LAC WEATHEREDGE

#### OUTCROPPINGS

##### DIMENSIONS

<b>US: inches</b>	<b>METRIC: mm</b>
l: 18" to 60"	l: 457 to 1524 mm
h: 5" to 12"	h: 127 to 304 mm
w: 18" to 60"	w: 457 to 1524 mm

note: lengths and widths are irregular shapes  
18 inches to 60 inches in diameter

### FOND DU LAC WEATHEREDGE

#### OUTCROPPINGS 5" to 8"

##### DIMENSIONS

<b>US: inches</b>	<b>METRIC: mm</b>
l: 18" to 60"	l: 457 to 1524 mm
h: 5" to 8"	h: 127 to 203 mm
w: 18" to 60"	w: 457 to 1524 mm

note: lengths and widths are irregular shapes  
18 inches to 60 inches in diameter

##### TYPICAL PIECE

ends irregular;  
natural cleft top and bottom;  
natural split sides with at least one face  
being seamface or weatheredge;  
stone is random shapes

## ASTM TESTING DATA

FOND DU LAC C97 water absorption—0.36%

FOND DU LAC C97 density—174.2 pcf

FOND DU LAC C99

modulus of rupture—1,470 psi

FOND DU LAC C170

compressive strength w/rift—29,040 psi

compressive strength across rift—34,240 psi

FOND DU LAC C880

flexural strength—1,740 psi



www.buechelstone.com