

PATIO & PAVING

MILL CREEK PATTERNED FLAGSTONE - THERMALLED



GEOLOGY: limestone

BASIC USE

on patios and walkways; stone is dryset in gravel (screenings) bed or mortared in

COLOR RANGE

wide mottled range of gray, pink, and tan; color variations common within a piece

COLOR CONSISTENCY PER PALLET

inconsistent

WEIGHT CALCULATED IN INCHES

l x w x h / 1728 (inches cubed) x 170
= approx 170 pounds per cubic foot

PALLET

as specified per project

PATIO & PAVING

COMMON COVERAGE *Est. (can vary)

2" height
80 square feet / ton

MILL CREEK PATTERNED FLAGSTONE-THERMALLED

DIMENSIONS

US: inches	METRIC: mm
l: 6" to 24"	l: 152 to 609 mm
h: 2"	h: 51 mm
w: 6" to 24"	w: 152 to 609 mm

note: ± 1/8" on sawn sides

PART NUMBERS

part number: N/A

PATIO & PAVING

MILL CREEK PATTERNED FLAGSTONE-THERMALLED

TYPICAL PIECE

ends square;
sawn and thermalled top;
sawn sides, face, and back;
natural cleft bottom;
stone is squares and rectangles

ASTM TESTING DATA

MILL CREEK C97 water absorption—0.66%
MILL CREEK C97 density—173.0 pcf
MILL CREEK C99
modulus of rupture—2,072 psi
MILL CREEK C170
compressive strength—26,260 psi
MILL CREEK C880 flexural strength—1,374 psi