

# STEPS

## MILL CREEK SNAPPED STEPS



**GEOLOGY:** dolomitic limestone

### BASIC USE

for steps

### COLOR RANGE

top or bottom buff to brown;  
face and sides light gray to buff  
with occasional blue veins

### COLOR CONSISTENCY PER PALLET

consistent

### WEIGHT CALCULATED IN INCHES

$l \times w \times h / 1728$  (inches cubed)  $\times 170$   
= approx 170 pounds per cubic foot

### PALLET

4,000 pounds

### STEPS PER PALLET

18" x 36" = 8 steps per pallet  
24" x 36" = 5 steps per pallet  
18" x 48" = 6 steps per pallet  
24" x 48" = 5 steps per pallet  
18" x 60" = 5 steps per pallet



## SNAPPED STEPS

### COVERAGES

coverages calculated as specified per project

### MILL CREEK 18"x36" SNAPPED STEPS

#### DIMENSIONS

US: inches	METRIC: mm
l: 35" to 37"	l: 889 to 939 mm
h: 5" to 8"	h: 127 to 203 mm
w: 17" to 19"	w: 431 to 482 mm

note:  $\pm 2"$  on split lengths and widths  
note:  $\pm 3"$  on natural cleft height

### MILL CREEK 24"x36" SNAPPED STEPS

#### DIMENSIONS

US: inches	METRIC: mm
l: 35" to 37"	l: 889 to 939 mm
h: 5" to 8"	h: 127 to 203 mm
w: 23" to 25"	w: 584 to 635 mm

note:  $\pm 2"$  on split lengths and widths  
note:  $\pm 3"$  on natural cleft height

### MILL CREEK 18"x48" SNAPPED STEPS

#### DIMENSIONS

US: inches	METRIC: mm
l: 47" to 49"	l: 1193 to 1244 mm
h: 5" to 8"	h: 127 to 203 mm
w: 17" to 19"	w: 431 to 482 mm

note:  $\pm 2"$  on split lengths and widths  
note:  $\pm 3"$  on natural cleft height

## PART NUMBERS

part number 18"x36": 1STELEN01002EA  
part number 24"x36": 1STELEN01004EA  
part number 18"x48": 1STELEN01001EA  
part number 24"x48": 1STELEN01006EA  
part number 18"x60": 1STELEN01007EA

## SNAPPED STEPS

### MILL CREEK 24"x48" SNAPPED STEPS

#### DIMENSIONS

US: inches	METRIC: mm
l: 47" to 49"	l: 1193 to 1244 mm
h: 5" to 8"	h: 127 to 203 mm
w: 23" to 25"	w: 584 to 635 mm

note:  $\pm 2"$  on split lengths and widths  
note:  $\pm 3"$  on natural cleft height

### MILL CREEK 18"x60" SNAPPED STEPS

#### DIMENSIONS

US: inches	METRIC: mm
l: 59" to 61"	l: 1499 to 1549 mm
h: 5" to 8"	h: 127 to 203 mm
w: 17" to 19"	w: 431 to 482 mm

note:  $\pm 2"$  on split lengths and widths  
note:  $\pm 3"$  on natural cleft height

#### TYPICAL PIECE

ends square;  
natural cleft top and bottom;  
split sides, face and back;  
stone is rectangular;  
custom sizing by request

## ASTM TESTING DATA

MILL CREEK C97 water absorption—0.66%  
MILL CREEK C97 density—173.0 pcf  
MILL CREEK C99  
modulus of rupture—2,072 psi  
MILL CREEK C170  
compressive strength—26,260 psi  
MILL CREEK C880 flexural strength—1,374 psi