

DIMENSIONAL

CHILTON TAILORED BLEND



GEOLOGY: dolomitic limestone

BASIC USE

exterior walls of buildings and fireplaces
stone shall be mortared in

COLOR RANGE

purple, lavender, mauve, gray,
buff, blue, and brown

COLOR CONSISTENCY PER PALLET

somewhat consistent

WEIGHT CALCULATED IN INCHES

l x w x h / 1728 (inches cubed) x 170
= approx 170 pounds per cubic foot

PALLET

FULL VENEER: 4,000 pounds

THIN VENEER: 10-15 lbs/ft²; Qty Bx or Sm Bx

Qty Bx - 100 sq ft flats and 50 lineal ft corners

Sm Bx - (24) 8 sq ft flats (192 sq ft) and

(20) 8 lineal ft corners (160 lineal ft)



FULL VENEER

COMMON COVERAGE ^{*Est.(can vary)}

Standard Joint	Drystack	Overgrout
40 square feet / ton	30 ft ² /ton	50 ft ² /ton

CHILTON TAILORED BLEND

DIMENSIONS

US: inches (average) METRIC: mm (average)

l: 6" to 42" (24") l: 152 to 1066 (609)

h: 2-1/4"; h: 5"; h: 57; h: 127;

h: 7-3/4"; h: 10-1/2" h: 196; h: 266

w: 3" to 5" (4") w: 76 to 127 (101)

note: ± 1/8" on sawn heights

ADDITIONAL SIZES

other heights available:

US: inches METRIC: mm

h: 13-1/4"; h: 16"; h: 336; h: 406;

h: 18-3/4"; h: 21-1/2" h: 476; h: 546

TYPICAL BLEND

20 percent 2-1/4"; 40 percent 5";

30 percent 7-3/4"; 10 percent 10-1/2"

TYPICAL PIECE

ends square;

sawn top and bottom; sides are split;

bedface face and back; stone is rectangular

in appearance with length longer than height

PART NUMBERS

FULL VENEER

part number: 1B8TBUE01010TN

THIN VENEER

qty bx flat: 1B8TBUE01005QB

sm bx flat: 1B8TBUE01005BX

qty bx corner: 1B8TBUE01505QB

sm bx corner: 1B8TBUE01505BX

50% ROCKFACED

please reference spec sheet specific to

Chilton Tailored Blend 50% Rockfaced

THIN VENEER

COMMON COVERAGE PER BOX ^{*Est.(can vary)}

Standard Joint	Drystack	Overgrout
8 & 100 square feet	6 & 75 ft ²	10 & 110 ft ²

CHILTON TAILORED BLEND

DIMENSIONS

US: inches (average) METRIC: mm (average)

l: 6" to 24" (12") l: 152 to 533 (304)

h: 2-1/4"; h: 5"; h: 57; h: 127;

h: 7-3/4"; h: 10-1/2" h: 196; h: 266

w: 3/4" to 1-1/4" (1") w: 19 to 31 (25)

corner return 3" to 5" cr: 76 to 127

note: ± 1/8" on sawn heights

ADDITIONAL SIZES

other heights available:

US: inches

h: 13-1/4"; h: 16";

h: 18-3/4"; h: 21-1/2"

TYPICAL BLEND

20 percent 2-1/4"; 40 percent 5";

30 percent 7-3/4"; 10 percent 10-1/2"

TYPICAL PIECE

ends square;

sawn top and bottom; sides are split;

bedface face and sawn back;

stone is rectangular in appearance

with length longer than height

ASTM TESTING DATA

CHILTON C97 water absorption—0.08%

CHILTON C97 density—177.4 pcf

CHILTON C99 modulus of rupture—1,220 psi

CHILTON C170

compressive strength w/rift—50,560 psi

compressive strength across rift—38,090 psi

CHILTON C880 flexural strength—3,070 psi



www.buechelstone.com