



LEDGESTONE

**EARTH WOOD
TAILORED
LEDGESTONE**

GEOLOGY: gneiss (form of granite)

BASIC USE

exterior walls of buildings and fireplaces
stone shall be mortared in

COLOR RANGE

charcoal green with
occasional brown and gold

COLOR CONSISTENCY PER PALLET

somewhat consistent

WEIGHT CALCULATED IN INCHES

$l \times w \times h / 1728$ (inches cubed) $\times 170$
= approx 170 pounds per cubic foot

PALLET

FULL VENEER: N/A (Natural Thin Veneer Only)
THIN VENEER: 10-15 lbs/ft²; Qty Bx or Sm Bx
Qty Bx - 100 sq ft flats and 50 lineal ft corners
Sm Bx - (24) 8 sq ft flats (192 sq ft) and
(20) 8 lineal ft corners (160 lineal ft)

FULL VENEER (N/A)

**EARTH WOOD TAILORED LEDGESTONE
NTV (NATURAL THIN VENEER) ONLY**

Earth Wood Tailored Ledgestone
is a Thin Veneer product only; so there is no
applicable Full Veneer spec information to
report.

Please find detailed data for this Thin Veneer
product listed below and in the other two
columns. Thank you.

PART NUMBERS

FULL VENEER
part number: N/A

THIN VENEER

qty bx flat: 1BTVBUE06002QB
sm bx flat: 1BTVBUE06002BX
qty bx corner: 1BTVBUE06502QB
sm bx corner: 1BTVBUE06502BX

THIN VENEER

COMMON COVERAGE PER BOX *Est.(can vary)

Figured for Drystacked Joint Only
8 & 100 square feet

EARTH WOOD TAILORED LEDGESTONE

DIMENSIONS

US: inches (average) METRIC: mm (average)

l: 4" to 16" (8") l: 102 to 406 (203)

h: 1"; h: 2"; h: 4" h: 25; h: 51; h: 102

w: 1/2" to 3/4" (5/8") w: 13 to 19 (16)

corner return N/A cr: N/A

CORNER INSTALLATION

THIN VENEER

EARTH WOOD TAILORED LEDGESTONE

TYPICAL BLEND

100 percent bedface face;
face of stone cannot have a sawn finish

TYPICAL PIECE

ends sawn random lengths;
sawn top, bottom, and sides;
back sawn; stone is linear
squares and rectangles



ASTM TESTING DATA

EARTH WOOD C97 water absorption—0.29%

EARTH WOOD C97 density—177.8 pcf

EARTH WOOD C170

compressive strength—15,530 psi



www.buechelstone.com