



ASHLAR
MILL CREEK
KENSINGTON
BLENDE

GEOLOGY: dolomitic limestone

BASIC USE

exterior walls of buildings and fireplaces
stone shall be mortared in

COLOR RANGE

70% Mill Creek Country Squire
30% Mill Creek Castle Rock
(THIN VENEER Castle Rock is 6" to 12")

COLOR CONSISTENCY PER PALLET

consistent

WEIGHT CALCULATED IN INCHES

l x w x h / 1728 (inches cubed) x 170
= approx 170 pounds per cubic foot

PALLET

FULL VENEER: 4,000 pounds
THIN VENEER: 10-15 lbs/ft²; Qty Bx or Sm Bx
Qty Bx - 100 sq ft flats and 50 lineal ft corners
Sm Bx - (24) 8 sq ft flats (192 sq ft) and
(20) 8 lineal ft corners (160 lineal ft)

FULL VENEER

COMMON COVERAGE *Est.(can vary)

Standard Joint	Drystack	Overgrout
40 square feet / ton	30 ft ² /ton	50 ft ² /ton

MILL CREEK COUNTRY SQUIRE

DIMENSIONS

US: inches (average)	METRIC: mm (average)
l: 6" to 42" (14")	l: 152 to 1066 (355)
h: 1/2" to 8"	h: 13 to 203
w: 3" to 5" (4")	w: 76 to 127 (101)

sides of stone shall be no less than 2-1/2 inches in width; stone shall not vary in height more than 1/2 an inch in a 12 inch span

TYPICAL PIECE

ends square; natural cleft top and bottom; back, face and sides split; stone is mostly rectangular

MILL CREEK CASTLE ROCK

DIMENSIONS

US: inches (average)	METRIC: mm (average)
l: 6" to 42" (16")	l: 152 to 1066 (406)
h: 4" to 12"	h: 13 to 203
w: 3" to 5" (4")	w: 76 to 127 (101)

stone shall not vary in height more than 1/2 an inch in a 12 inch span

TYPICAL PIECE

ends square; split top, bottom, and sides; bedface face and back; stone is squares and rectangles

PART NUMBERS

FULL VENEER

part number: 1BSTLEN01011TN

THIN VENEER

qty bx flat: 1BTVLEN01011QB
sm bx flat: 1BTVLEN01011BX
qty bx corner: 1BTVLEN01511QB
sm bx corner: 1BTVLEN01511BX

THIN VENEER

COMMON COVERAGE PER BOX *Est.(can vary)

Standard Joint	Drystack	Overgrout
8 & 100 square feet	6 & 75 ft ²	10 & 110 ft ²

MILL CREEK COUNTRY SQUIRE

DIMENSIONS

US: inches (average)	METRIC: mm (average)
l: 6" to 24" (12")	l: 152 to 533 (304)
h: 1/2" to 8"	h: 12 to 203
w: 3/4" to 1-1/4" (1")	w: 19 to 31 (25)

corner return 3" to 5" cr: 76 to 127
stone shall not vary in height more than 1/2 an inch in a 12 inch span

TYPICAL PIECE

ends square; natural cleft top and bottom; face and sides split; sawn back; stone is mostly rectangular

MILL CREEK CASTLE ROCK

DIMENSIONS

US: inches (average)	METRIC: mm (average)
l: 6" to 24" (12")	l: 152 to 533 (304)
h: 4" to 12"	h: 101 to 304
w: 3/4" to 1-1/4" (1")	w: 19 to 31 (25)

corner return 3" to 5" cr: 76 to 127
stone shall not vary in height more than 1/2 an inch in a 12 inch span

TYPICAL PIECE

ends square; split top, bottom, and sides; bedface face and sawn back; stone is squares and rectangles

ASTM TESTING DATA

MILL CREEK C97 water absorption—0.66%
MILL CREEK C97 density—173.0 pcf
MILL CREEK C99
modulus of rupture—2,072 psi
MILL CREEK C170
compressive strength—26,260 psi
MILL CREEK C880 flexural strength—1,374 psi



www.buechelstone.com