

LEDGESTONE

WALNUT TAILORED LEDGESTONE



GEOLOGY: gneiss (form of granite)

BASIC USE

exterior walls of buildings and fireplaces
stone shall be mortared in

COLOR RANGE

burnt tones, grays,
browns, and tans

COLOR CONSISTENCY PER PALLET

somewhat consistent

WEIGHT CALCULATED IN INCHES

$l \times w \times h / 1728$ (inches cubed) $\times 170$
= approx 170 pounds per cubic foot

PALLET

FULL VENEER: N/A (Natural Thin Veneer Only)
THIN VENEER: 10-15 lbs/ft²; Qty Bx or Sm Bx
Qty Bx - 100 sq ft flats and 50 lineal ft corners
Sm Bx - (24) 8 sq ft flats (192 sq ft) and
(20) 8 lineal ft corners (160 lineal ft)



FULL VENEER (N/A)

WALNUT TAILORED LEDGESTONE NTV (NATURAL THIN VENEER) ONLY

Walnut Tailored Ledgestone is a
Thin Veneer product only; so there is no
applicable Full Veneer spec information to
report.

Please find detailed data for this Thin Veneer
product listed below and in the other two
columns. Thank you.

THIN VENEER

WALNUT TAILORED LEDGESTONE

TYPICAL BLEND

100 percent bedface face;
face of stone cannot have a sawn finish

TYPICAL PIECE

ends sawn random lengths;
sawn top, bottom, and sides;
back sawn; stone is linear
squares and rectangles

PART NUMBERS

FULL VENEER
part number: N/A

THIN VENEER

qty bx flat: 1BTVBUE06011QB
sm bx flat: 1BTVBUE06011BX
qty bx corner: 1BTVBUE06511QB
sm bx corner: 1BTVBUE06511BX

THIN VENEER

COMMON COVERAGE PER BOX *Est.(can vary)

Figured for Drystacked Joint Only
8 & 100 square feet

WALNUT TAILORED LEDGESTONE

DIMENSIONS

US: inches (average) METRIC: mm (average)

l: 4" to 16" (8") l: 102 to 406 (203)

h: 1"; h: 2"; h: 4" h: 25; h: 51; h: 102

w: 1/2" to 3/4" (5/8") w: 13 to 19 (16)

corner return N/A cr: N/A

CORNER INSTALLATION



ASTM TESTING DATA

WALNUT C97 water absorption—0.29%

WALNUT C97 density—177.8 pcf

WALNUT C170

compressive strength—15,530 psi

