

TAILORED FIELDLEDGE

BLACK FROST TAILORED FIELDLEDGE



GEOLOGY: quartzitic sandstone

BASIC USE

exterior walls of buildings and fireplaces
stone shall be mortared in

COLOR RANGE

blacks, charcoals, grays, blues, whites with
occasional greens, buffs, and browns

COLOR CONSISTENCY PER PALLET

somewhat consistent

WEIGHT CALCULATED IN INCHES

$l \times w \times h / 1728$ (inches cubed) $\times 170$
= approx 170 pounds per cubic foot

PALLET

FULL VENEER: N/A (Natural Thin Veneer Only)
THIN VENEER: 10-15 lbs/ft²; Qty Bx or Sm Bx
Qty Bx - 100 sq ft flats and 50 lineal ft corners
Sm Bx - (24) 8 sq ft flats (192 sq ft) and
(20) 8 lineal ft corners (160 lineal ft)

FULL VENEER (N/A)

BLACK FROST TAILORED FIELDLEDGE

NTV (NATURAL THIN VENEER) ONLY

Black Frost Tailored Fieldledge is a Thin Veneer product only; so there is no applicable Full Veneer spec information to report. Please find detailed data for this Thin Veneer product listed in the far right column. Thank you.



PART NUMBERS

FULL VENEER

part number: N/A

THIN VENEER

qty bx flat: 1BTVGRA03063QB
sm bx flat: 1BTVGRA03063BX
qty bx corner: 1BTVGRA03563QB
sm bx corner: 1BTVGRA03563BX

ASTM TESTING DATA

BLACK FROST C97

water absorption—0.2%

BLACK FROST C97

specific gravity—3.051

BLACK FROST C97

density—190.4 pcf

BLACK FROST C99

modulus of rupture dry—3,040 psi

modulus of rupture wet—2,610 psi

BLACK FROST C170

compressive strength parallel dry—15,070 psi

compressive strength parallel

wet—12,070 psi

compressive strength perpendicular

dry—25,340 psi

compressive strength perpendicular

wet—15,070 psi

THIN VENEER

COMMON COVERAGE PER BOX *Est.(can vary)

Figured for Drystack Joint Only

8 & 100 square feet

BLACK FROST TAILORED FIELDLEDGE

DIMENSIONS

US: inches (average) METRIC: mm (average)

l: 3" to 24" dia. l: 76 to 610 dia.

h: 2"; h: 4"; h: 6" h: 51; h: 102; h: 152

w: 3/4" to 1-1/4" (1") w: 19 to 31 (25)

corner return N/A cr: N/A

note: sawn heights with varying lengths
having rough irregular ends

TYPICAL PIECE

ends irregular; random lengths;

sawn top and bottom; sides not square;

bedface face and sawn back;

overall appearance of stone will be linear

when installed

CORNER INSTALLATION

