WALL STONE

CHILTON GARDEN STONE AND CHILTON SHIMS





GEOLOGY: dolomitic limestone

BASIC USE

aids in the installation of wall stone to help level layers on the wall; also used for retaining ground on small walls; and as a stepping stone

COLOR RANGE

purple, lavender, mauve, gray, buff, blue, and brown

COLOR CONSISTENCY PER PALLET

inconsistent

WEIGHT CALCULATED IN INCHES

I x w x h / 1728 (inches cubed) x 170 = approx 170 pounds per cubic foot

PALLET

Garden Stone: 100 pieces per box Shims: 4,000 pounds

WALL STONE

COMMON COVERAGE *Est.(can vary)

stepping stone wall stone 75 square feet / ton 30 ft²/ton

CHILTON GARDEN STONE AND SHIMS

DIMENSIONS _____

US: inches METRIC: mm
I: 4" to 10" I: 101 to 245 mm
h: 3/4" to 3" h: 19 to 76 mm
w: 4" to 10" w: 101 to 245 mm
note: lengths and widths are irregular shapes

4 inches to 10 inches in diameter



PART NUMBERS

part no. garden stone: 1RWSBUE01001BX part no. shims: 1RWSBUE01501TN

WALL STONE

CHILTON GARDEN STONE AND SHIMS

TYPICAL PIECE ends irregular; natural cleft top and bottom; natural split sides; stone is random shapes

ASTM TESTING DATA

CHILTON C97 water absorption—0.08%
CHILTON C97 density—177.4 pcf
CHILTON C99 modulus of rupture—1,220 psi
CHILTON C170

compressive strength w/rift—50,560 psi compressive strength across rift—38,090 psi CHILTON C880 flexural strength—3,070 psi

