

## STEPS

### CHILTON OUTCROPPING STEPS



**GEOLOGY:** dolomitic limestone

**BASIC USE**  
for steps

**COLOR RANGE**

top or bottom is purple, lavender, mauve, gray, buff, blue, and brown; face is gray to charcoal with occasional mauves

**COLOR CONSISTENCY PER PALLET**  
somewhat consistent

**WEIGHT CALCULATED IN INCHES**

l x w x h / 1728 (inches cubed) x 170  
= approx 170 pounds per cubic foot

**PALLET**  
4,000 pounds



### OUTCROPPING STEPS

**COVERAGES**

coverages calculated as specified per project

### CHILTON OUTCROPPING STEPS

**DIMENSIONS**

US: inches

METRIC: mm

l: 18" to 60"

l: 457 to 1524 mm

h: 5" to 8"

h: 127 to 203 mm

w: 18" to 60"

w: 457 to 1524 mm

note: lengths and widths are irregular shapes  
18 inches to 60 inches in diameter

### PART NUMBERS

part number: 1OUTBUE01006TN

### OUTCROPPING STEPS

**CHILTON OUTCROPPING STEPS**

**TYPICAL PIECE**

ends irregular;  
natural cleft top and bottom;  
natural split sides;  
stone is somewhat square but  
may be irregular

### ASTM TESTING DATA

CHILTON C97 water absorption—0.08%

CHILTON C97 density—177.4 pcf

CHILTON C99 modulus of rupture—1,220 psi

CHILTON C170

compressive strength w/rift—50,560 psi

compressive strength across rift—38,090 psi

CHILTON C880 flexural strength—3,070 psi

