



PATIO & PAVING

FOND DU LAC
COLONIAL
PAVERS

GEOLOGY: dolomitic limestone

BASIC USE

exterior walls of buildings and fireplaces
stone shall be mortared in

COLOR RANGE

gray, light gray, buff, and white;
white from tumbling

COLOR CONSISTENCY PER PALLET

consistent

WEIGHT CALCULATED IN INCHES

l x w x h / 1728 (inches cubed) x 170
= approx 170 pounds per cubic foot

PALLET

FULL VENEER: 4,000 pounds
THIN VENEER: 10-15 lbs/ft²; Qty Bx or Sm Bx
Qty Bx - 100 sq ft flats and 50 lineal ft corners
Sm Bx - (24) 8 sq ft flats (192 sq ft) and
(20) 8 lineal ft corners (160 lineal ft)

FULL VENEER

COMMON COVERAGE ^{*Est.(can vary)}

Standard Joint	Drystack	Overgrout
35 square feet / ton	25 ft ² /ton	45 ft ² /ton

FOND DU LAC COLONIAL PAVERS

DIMENSIONS

US: inches (average) METRIC: mm (average)

l: 5" or 10" l: 127 or 254

h: 5" h: 127

w: 3" to 5" (4") w: 76 to 127 (101)

note: ± 1/8" on sawn heights

TYPICAL PIECE

ends square;
sawn top and bottom;
sides are split;
bedface face and back;
back may be sawn;
stone rounded from tumbling

PART NUMBERS

FULL VENEER

part number 5"x 5"x 4": 1PAVBUE02007TN
part number 5"x 5"x 5": 1PAVBUE02009TN
part number 5"x 10"x 4": 1PAVBUE02008TN
part number 5"x 10"x 5": 1PAVBUE02010TN

THIN VENEER

qty bx flat: 1BTVBUE02041QB
sm bx flat: 1BTVBUE02041BX
qty bx corner: 1BTVBUE02518QB
sm bx corner: 1BTVBUE02528BX

THIN VENEER

COMMON COVERAGE PER BOX ^{*Est.(can vary)}

Standard Joint	Drystack	Overgrout
8 & 100 square feet	6 & 75 ft ²	10 & 110 ft ²

FOND DU LAC COLONIAL PAVERS

DIMENSIONS

US: inches (average) METRIC: mm (average)

l: 5" or 10" l: 127 or 254

h: 5" h: 127

w: 3/4" to 1-1/4" (1") w: 19 to 31 (25)

corner return 3" to 5" cr: 76 to 127

note: ± 1/8" on sawn heights

TYPICAL PIECE

ends square;
sawn top and bottom;
sides are split;
bedface face and sawn back;
stone rounded from tumbling

ASTM TESTING DATA

FOND DU LAC C97 water absorption—0.36%

FOND DU LAC C97 density—174.2 pcf

FOND DU LAC C99

modulus of rupture—1,470 psi

FOND DU LAC C170

compressive strength w/rift—29,040 psi

compressive strength across rift—34,240 psi

FOND DU LAC C880

flexural strength—1,740 psi

