



WALL STONE

**FOND DU LAC
WEATHEREDGE
WALL STONE**

GEOLOGY: dolomitic limestone

BASIC USE

for retaining ground;
stone is typically dryset (no mortar used)
when installed

COLOR RANGE

gray, light gray to white, buff;
face is brown, buff, tan, and gold

COLOR CONSISTENCY PER PALLET

consistent

WEIGHT CALCULATED IN INCHES

$l \times w \times h / 1728$ (inches cubed) $\times 170$
= approx 170 pounds per cubic foot

PALLET

4,000 pounds

SNAPPED WALL STONE

COMMON COVERAGE ^{*Est.(can vary)}

6 inch	8 inch	12 inch
30 square feet / ton	20 ft ² /ton	15 ft ² /ton

FOND DU LAC WEATHEREDGE

8" DIMENSIONS

US: inches (average) **METRIC: mm (average)**

l: 6" to 42" (16") l: 152 to 1066 (406)

w: 7" to 9" (8") w: 177 to 228 (203)

note: sides of stone shall be no less than

2-1/2 inches (63 mm) in width

12" DIMENSIONS

US: inches (average) **METRIC: mm (average)**

l: 6" to 42" (16") l: 152 to 1066 (406)

w: 11" to 13" (12") w: 279 to 482 (304)

note: sides of stone shall be no less than

2-1/2 inches (63 mm) in width

HEIGHTS DIMENSIONS

US: inches (average) **METRIC: mm (average)**

2-5": 1-1/2" to 5-1/2" h: 38 mm to 139 mm

2-3": 1-1/2" to 3-1/2" h: 38 mm to 89 mm

3-4": 2-1/2" to 4-1/2" h: 63 mm to 114 mm

4-5": 3-1/2" to 5-1/2" h: 89 mm to 139 mm

5-7": 4-1/2" to 7-1/2" h: 114 mm to 190 mm

TYPICAL PIECE

ends square;

natural cleft top and bottom;

split sides and back;

face is seamface or weatheredge;

stone is mostly rectangular

PART NUMBERS

SNAPPED

part number 6" (2"-5"): 1RWSBUE02203TN

part number 8" (2"-5"): 1RWSBUE02106TN

part number 8" (2"-3"): 1RWSBUE02113TN

part number 8" (3"-4"): 1RWSBUE02114TN

part number 8" (4"-5"): 1RWSBUE02115TN

part number 8" (5"-7"): 1RWSBUE02110TN

part number 12" (2"-5"): 1RWSBUE02005TN

part number 12" (5"-7"): 1RWSBUE02012TN

RANDOM

part number 2"-5": 1RWSBUE02403TN

part number 5"-7": 1RWSBUE02407TN

RANDOM WALL STONE

COMMON COVERAGE ^{*Est.(can vary)}

Random Wall Stone

15 square feet

FOND DU LAC WEATHEREDGE

2" to 5" DIMENSIONS

US: inches

METRIC: mm

l: 6" to 30"

l: 152 to 762

h: 1-1/2" to 5-1/2"

h: 38 to 139

w: 6" to 30"

w: 152 to 762

note: lengths and widths are irregular shapes

6 inches to 30 inches in diameter

5" to 7" DIMENSIONS

US: inches

METRIC: mm

l: 6" to 30"

l: 152 to 762

h: 4-1/2" to 7-1/2"

h: 114 to 190

w: 6" to 30"

w: 152 to 762

note: lengths and widths are irregular shapes

6 inches to 30 inches in diameter

TYPICAL PIECE

ends irregular;

natural cleft top and bottom;

natural split sides with at least one

face being seamface or weatheredge;

stone is random shapes

ASTM TESTING DATA

FOND DU LAC C97 water absorption—0.36%

FOND DU LAC C97 density—174.2 pcf

FOND DU LAC C99

modulus of rupture—1,470 psi

FOND DU LAC C170

compressive strength w/rift—29,040 psi

compressive strength across rift—34,240 psi

FOND DU LAC C880

flexural strength—1,740 psi



www.buechelstone.com