



WALL STONE

JUTE CLOTH WALL STONE

GEOLOGY: limestone

BASIC USE

for retaining ground;
stone is typically dryset (no mortar used)
when installed

COLOR RANGE

light grays to buffs with occasional blue veins

COLOR CONSISTENCY PER PALLET

consistent

WEIGHT CALCULATED IN INCHES

l x w x h / 1728 (inches cubed) x 125.1
= approx 125.1 pounds per cubic foot

PALLET

3,000 - 4,000 pounds

PART NUMBERS

part number 8" (2"-7") : 1RWSKNS03001TN

SNAPPED WALL STONE

COMMON COVERAGE *Est.(can vary)

8 inch

20 square feet / ton

JUTE CLOTH WALL STONE

8" DIMENSIONS

US: inches (average) METRIC: mm (average)

l: 6" to 42" (16") l: 152 to 1066 (406)

h: 1-1/2" to 7-1/2" h: 38 to 190

w: 7"-9" (8") w: 177 to 228

note: sides of stone shall be no less than 2 1/2"
(63 mm) in width

JUTE CLOTH WALL STONE

TYPICAL PIECE

ends square;

natural cleft top and bottom;

split sides, face, and back;

stone is mostly rectangular

ASTM TESTING DATA

JUTE CLOTH C97 water absorption—10.03%

specific gravity — 1.995 to 2.008

density—125.1 lbs/ft³

JUTE CLOTH C170

dry perpendicular—4,040 psi

wet perpendicular—1,830 psi

dry parallel —3,210 psi

wet parallel—1,480 psi

JUTE CLOTH C880

flexural strength -wet —440 psi

flexural strength -dry —600 psi

