

OUTCROPPINGS

SILVERDALE HAND CUT BEAMS



GEOLOGY: limestone

BASIC USE

for retaining ground or
as an accent in landscaping

COLOR RANGE

yellows and creams to slight buffs with
occasional veining

COLOR CONSISTENCY PER PALLET

consistent

WEIGHT CALCULATED IN INCHES

$l \times w \times h / 1728$ (inches cubed) $\times 170$
= approx 134 pounds per cubic foot

PALLET

3,000 - 4,000 pounds

SAWN BEAMS

SILVERDALE SAWN BEAMS

TYPICAL PIECE

ends irregular; natural cleft top and bottom;
natural split, seamface, or weatheredge sides,
stone hand-split for one straight edge



PART NUMBERS

part number: 1BEAKNS01001TN

SAWN BEAMS

COVERAGES

coverages calculated as specified per project

SILVERDALE SAWN BEAMS

DIMENSIONS

US: inches
l: 24" to 60"
h: 10" - 16"
w: 18" to 24"

METRIC: mm
l: 609 to 1524 mm
h: 254 to 406 mm
w: 457 to 609 mm

ASTM TESTING DATA

SILVERDALE C97 water absorption—7.27%
SILVERDALE C97 density—134.1 pcf
SILVERDALE C97 specific gravity—2.149
SILVERDALE C99
modulus of rupture—1,174 psi
SILVERDALE C170
compressive strength —6,631 psi
SILVERDALE C241
abrasion resistance—5.38



www.buechelstone.com