

STEPS

SILVERDALE

SAWN STEPS



GEOLOGY: limestone

BASIC USE

for steps

COLOR RANGE

yellows and creams to slight buffs and cool grays

COLOR CONSISTENCY PER PALLET

inconsistent

WEIGHT CALCULATED IN INCHES

l x w x h / 1728 (inches cubed) x 160
= approx 134 pounds per cubic foot

PALLET

2,000 to 3,000 pounds

STEPS PER PALLET

18" x 36" = 8 steps per pallet

18" x 48" = 6 steps per pallet

24" x 36" = 5 steps per pallet

24" x 48" = 5 steps per pallet



SAWN STEPS

SILVERDALE 18"x36" SAWN STEPS

DIMENSIONS

US: inches

l: 35" to 37"

h: 6"

w: 17" to 19"

note: sawn to 6" height

note: ± 1/4" on height

METRIC: mm

l: 889 to 940 mm

h: 152 mm

w: 431 to 482 mm

SILVERDALE 18"x48" SAWN STEPS

DIMENSIONS

US: inches

l: 47" to 49"

h: 6"

w: 17" to 19"

note: sawn to 6" height

note: ± 1/4" on height

METRIC: mm

l: 1194 to 1244 mm

h: 152 mm

w: 431 to 482 mm

TYPICAL PIECE

ends square;

sawn top and bottom;

split sides, face and back;

stone is rectangular;

custom sizing by request

PART NUMBERS

part number 18"x36": 1STEKNS01001EA

part number 18"x48": 1STEKNS01002EA

part number 24"x36": 1STEKNS01003EA

part number 24"x48": 1STEKNS01004EA

SAWN STEPS

SILVERDALE 24"x36" SAWN STEPS

DIMENSIONS

US: inches

l: 35" to 37"

h: 6"

w: 23" to 25"

note: sawn to 6" height

note: ± 1/4" on height

METRIC: mm

l: 889 to 940 mm

h: 152 mm

w: 584 to 635 mm

SILVERDALE 24"x48" SAWN STEPS

DIMENSIONS

US: inches

l: 47" to 49"

h: 6"

w: 23" to 25"

note: sawn to 6" height

note: ± 1/4" on height

METRIC: mm

l: 1194 to 1244 mm

h: 152 mm

w: 584 to 635 mm

TYPICAL PIECE

ends square;

sawn top and bottom;

split sides, face and back;

stone is rectangular;

custom sizing by request

ASTM TESTING DATA

SILVERDALE C97 water absorption—7.27%

SILVERDALE C97 density—134.1 pcf

SILVERDALE C97 specific gravity—2.149

SILVERDALE C99

modulus of rupture—1,174 psi

SILVERDALE C170

compressive strength —6,631 psi

SILVERDALE C241

abrasion resistance—5.38



www.buechelstone.com